

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

of
The Dependent Resurvey of

PORTIONS OF THE WEST AND NORTH BOUNDARIES

AND A

PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 4, 5, 10, 15, 18, AND 19,

IN

TOWNSHIP 14 SOUTH, RANGE 1 WEST

of the SALT LAKE Meridian
In the State of UTAH

EXECUTED BY

M. Ross Workman and Ronald K. Baugh
Supervisory Cadastral Surveyors

Under special instructions dated *August 30, 1996*, approved August 30, 1996, which provided for the surveys included under Group Number 860, and assignment instructions dated *October 4, 1996*.

Survey commenced *October 7, 1996*

Survey completed *October 24, 1997*

INDEX DIAGRAM

Township 14 South, Range 1 West

		8	6	5		
	6	5	4	3	2	1
		14	13	13		
	7	8	9	10	11	12
				13	11	
	18	17	16	15	14	13
	16		12	11	9	
4						
	19	20	21	22	23	24
	15					
3						
	30	29	28	27	26	25
2						
	31	32	33	34	35	36

The Subdivision of Section 4	Page 18
The Subdivision of Section 5	Page 20
The Subdivision of Section 10	Page 21
The Subdivision of Section 15	Page 23
The Subdivision of Section 18	Page 24
The Subdivision of Section 19	Page 30

TOWNSHIP 14 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the north and west boundaries, and a portion of the subdivisional lines, and the subdivision of sections 4, 5, 10, 15, 18, and 19 in Township 14 South, Range 1 West, Salt Lake Meridian, Utah.

History of Surveys**Surveyed by****Retr. or Resurveyed by****NORTH BOUNDARY**

Portion	C. Mogo	1856		
Portion	E.W. Koeber	1884	E.W. Koeber	1884
Portion	Stewart and Stewart	1898	Stewart and Stewart	1898
Portion			R. Zaninovich	1991-92

SOUTH BOUNDARY

Portion	C. Mogo	1856		
Portion	Stewart and Stewart	1898	Stewart and Stewart	1898
Portion			F.D. Reynolds	1993-94

EAST BOUNDARY

All	C. Mogo	1856		
All			A.D. Ferron	1882

WEST BOUNDARY

Portion	F. Dickert	1871		
Portion	Stewart and Stewart	1898		
All			Stewart and Heist	1912
Portion			R.A. Zaninovich	1991
Portion			F.D. Reynolds	1993-94

SUBDIVISION

Portion	C. Mogo	1856		
Portion	Stewart and Stewart	1898	Stewart and Stewart	1898
Portion			R.A. Zaninovich	1991
Portion			F.D. Reynolds	1993-94

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 860, Utah, dated August 30, 1996.

Preliminary to the resurvey, a diligent search was made for any evidence of the original field note record. Coordinates by the use of Global Positioning System (G.P.S.) equipment were determined for each found and proportioned corner in this survey. True bearings and distances were calculated by inverting between these points.

TOWNSHIP 14 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The geographic position of the section corner of sections 14, 15, 22, and 23, T. 14 S., R. 1 W., which will also function as a B.L.M. Control Station, was determined by G.P.S. methods, from national Geodetic Survey Triangulation Station "SHARP", (1986 adjustment), is as follows:

Latitude 39° 35' 12.376" N. Longitude 111° 54' 38.248" W.
N.A.D. 1983

The geographic position of the 1/4 section corner of sections 19 and 20, T. 14 S., R. 1 W., which will also function as a B.L.M. Control Station, was determined by G.P.S. methods, from National Geodetic Survey Triangulation Station "CAPPS", (1886 adjustment), is as follows:

Latitude 39° 34' 43.420" N. Longitude 111° 57' 58.423" W.
N.A.D. 1983

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: 13 3/4° East.

Dependent Resurvey of a Portion of the West Boundary,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by F. Dickert in 1871,
the Survey and Resurvey by Stewart and Stewart in 1898,
the Resurvey by Stewart and Heist in 1912,
the Resurvey by R. A. Zaninovich in 1991,
and the Resurvey by F.D. Reynolds in 1993

Beginning at the 1/4 section corner of section 25 only, T. 14 S., R. 2 W., monumented with a 1986 Juab County aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, firmly set, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 03'.7' W., on the east boundary of section 25, T. 14 S., R. 2 W.

- 10.788** The closing corner of sections 19 and 30, monumented with a 1986 Juab County aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, firmly set, with aluminum cap marked as described in the official record of the 1993 resurvey.
- 30.603** Point for the S 1/16 section corner of section 19 only, on the west boundary of the township; not monumented.
- 40.053** The corner of sections 24 and 25, T. 14 S., R. 2 W., monumented with a 1986 Juab County aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, firmly set, with aluminum cap marked as described in the official record of the 1993 resurvey.
-

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 24.7' E., on the east boundary of section 24, T. 14 S., R. 2 W.

10.365

Point for the 1/4 section corner of section 19 only, T. 14 S., R. 1 W.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S
R2W R1W
| 1/4 S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

30.180

Point for the N 1/16 section corner of section 19 only, on the west boundary of the township; not monumented.

40.183

The 1/4 section corner of section 24 only, T. 14 S., R. 2 W., monumented with a 1986 Juab County aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, firmly set in a collar of stone, in a N and S fence line, with aluminum cap marked:

JUAB COUNTY
T14S
R2W 1/4 | R1W
S24 |
1986

This corner is accepted as the best available evidence of the original corner position.

N. 0° 01.3' E., beginning new measurement.

9.812

True point for the closing corner of sections 18 and 19.

20.090

Point for the N 1/16 section corner of section 24 only, T. 14 S., R. 2 W.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T14S
R2W R1W
N 1/16 |
S24 |
1996

Set a 6 ft. steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

29.672

Point for the S 1/16 section corner of section 18 only. Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a collar of stone, with aluminum cap marked:

T14S
R2W R1W
| S 1/16
| S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.180

The corner of sections 13 and 24 only, T. 14 S., R. 2 W., monumented with a 1996 Juab County aluminum post, 2 1/2 inches diameter, set firmly in the ground, and steel fence post alongside, with aluminum cap marked:

JUAB COUNTY
T14S
R2W R1W
13 | 18
24 |
1986

This corner is accepted as the best available evidence of the original corner position.

N. 0° 10.6' W., on the east boundary of section 13, T. 14 S., R. 2 W.

9.352

Point for the 1/4 section corner of section 18 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S
R2W R1W
| 1/4
| S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

29.212

Point for the N 1/16 section corner of section 18 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, 4 ft. base, 1 ft. high, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S
R2W R1W
| N 1/16
| S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

- 40.064** The 1/4 section corner of section 13 only, T. 14 S., R. 2 W., monumented with an aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, firmly set, in a collar of stone, and in a mound of stone to the west, with aluminum cap marked as described in the official record of the 1991 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 09.8' W., beginning new measurement.

- 9.008** The closing corner of sections 7 and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, and a mound of stone to the east, with aluminum cap marked as described in the official record of the 1991 resurvey.

From this corner, the corner of sections 12 and 13 only, T. 14 S., R. 2 W., monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, a steel fence post alongside the aluminum post, and a N and S fence located 3 ft. east, with aluminum cap marked as described in the official record of the 1991 resurvey, bears N. 0° 09.8' W., 30.965 chs. dist.

Dependent Resurvey of a Portion of the North Boundary,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by E.W. Koeber in 1884,
and the Resurvey Executed by Stewart and Stewart in 1898

From the corner of sections 34 and 35 only, on the south boundary of T. 13 S., R. 1 W., monumented with a Juab County aluminum post, 2 1/2 inches diameter, firmly set in a mound of stone, with 3 ft. base to top of aluminum cap marked:

JUAB COUNTY
T13S
R1W S34 | S35 1986
T14S

Set a 6 ft. steel fence post alongside the aluminum post.

This corner is accepted as the best available evidence of the original corner position.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

No other improvements were made to this monument.

Corner is located south, 10 ft. from old fence corner, bears E, W, and S.

S. 89° 14.6' W., on the south boundary of section 34, T. 13 S., R. 1 W.

40.152 Point for the south 1/4 section corner of section 34, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

77.572 Point for the closing corner of sections 3 and 4, T. 14 S., R. 1 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

T13S R1W	
<u>S34</u>	
S4	S3
C	C
T14S	
1997	

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the corner.

Corner is located on a southerly and rocky slope, among juniper trees.

80.304 Point for the corner of sections 33 and 34 only, T. 13 S., R. 1 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

T13S R1W	
<u>S33</u>	<u>S34</u>
S4	
T14S	
1997	

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

Corner is located on a southerly rocky slope in juniper.

S. 89° 14.6' W., on the south boundary of section 33, T. 13 S., R. 1 W.

36.938 Point for the north 1/4 section corner of section 4, T. 14 S., R. 1 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S
 1/4 S4
 T14S R1W
 T14S
 1997

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the corner.

Corner is located on a NE slope in rocks and juniper.

40.326 Point for the south 1/4 section corner of section 33, T. 13 S., R. 1 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R1W
1/4 S33
 T14S
 1997

Raise a mound of stone, 5 ft. base, 2 ft. high, north of the corner.

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on a NE slope among scattered junipers, and 30 lks. north of barbed wire fence, bears E and W.

76.608 Point for the closing corner of sections 4 and 5, T. 14 S., R. 1 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R1W
S35
 C | C
 S5 | S4
 T14S
 1997

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on a flat and grassy area that has been cleared of rocks as part of a reseeding project.

80.652 Point for the corner of sections 32 and 33 only, T. 13 S., R. 1 W., at proportionate distance.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A quartzite stone, 10x8x12 inches, with 4 grooves on the east and 2 grooves on the W edges, was found near proportioned point in rock pile, caused by chaining for a reseeding project. This position was not accepted as the original corner position because it has been moved.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R1W
S32 | S33
S5
T14S
1997

Bury a quartzite stone on north side of the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

S. 89° 14.6' W., on the south boundary of section 32, T. 13 S., R. 1 W.

35.748 Point for the north 1/4 section corner of section 5, T. 14 S., R. 1 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S
1/4 S5
T14S R1W
1997

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the corner.

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on SW slope in grass and juniper, and about 1 chain east of draw, drains S. 40° W.

40.192 The south 1/4 section corner of section 32, T. 13 S., R. 1 W., monumented with a granite stone, 13x10x8 inches, firmly set, and plainly marked with 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S R1W
1/4 S32
1997

Deposit the marked stone alongside the aluminum post.

S. 89° 03.7' W., beginning new measurement.

35.348 Point for the closing corner of sections 5 and 6, T. 14 S., R. 1 W., at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 3 1/2 ft. diameter, to top of aluminum cap marked:

T13S R1W
S32
C | C
S6 | S5
T14S R1W
1997

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 30 ft. north of 18 ft. wide gravel road that curves from east to south.

Corner is south of barbed wire fence that bears E and W, in sagebrush and scattered juniper.

40.163 The corner of sections 31 and 32, monumented with an aluminum post, 2 1/2 ins diameter, firmly set in a mound of stone, to top of aluminum cap marked as described in the official record of the 1992 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by C. Mogo in 1856
and the Resurvey Executed by Stewart and Stewart in 1898

From the corner of sections 14, 15, 22, and 23, monumented with a quartzite stone, 16x10x7 inches, poorly marked and laying loose in a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W
S15 | S14
S22 | S23
1997

A Deep-1 Magnet was buried at base of aluminum post.

Bury marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, north of the corner.

Corner is located in a flat farm pasture area.

N. 0° 35.7' W., between sections 14 and 15.

39.879 Point for the 1/4 section corner of sections 14 and 15, at proportionate distance by the irregular boundary method; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
1/4
S15 | S14
1997

Set a 6 ft. steel fence post alongside the aluminum post.

From this corner, a 5/8 in. rebar of undetermined origin, protruding 5 inches above ground, with aluminum cap marked 82R, bears N. 6° 28.1' W., 1.550 chains distance.

N. 0° 39.1' W., beginning new measurement.

40.100 The corner of sections 10, 11, 14, and 15, as determined from a tie made by Utah Department of Transportation in 1977, Project Number 1-15-5(11)213, sheet Number 18. This corner falls in the pavement of the north bound lane.

At the corner point

Set a spike, 8 inches long, 1/4 inch diameter, flush with the pavement.

From this point, a right-of-way marker, monumented with a 2 inch cap, set in concrete, marked CL200 ST 468 + 18.46 1985, bears N. 47° 05.2' E., 4.272 chains distance. This right-of-way marker will also function as a reference monument for the section corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From this same point, a right-of-way marker, monumented with a 2 inch cap, set in concrete, marked C L200 ST 458+47.12 1985, bears S. 18° 04.7' W., 10.833 chains distance. This right-of-way marker will also function as a reference monument for the section corner.

N. 1° 43.7' W., between sections 10 and 11.

40.877 Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, falls on private farm land; not monumented.

81.754 The corner of sections 2, 3, 10, and 11, monumented with a Juab County aluminum post, 2 inches diameter, firmly set in a mound of stone, with marked stone on north side of post, with aluminum cap marked:

JUAB COUNTY		
S3	S2	
S10	S11	1986

Corner is located at a fence corner from which fences bears N and E.

This corner is accepted as a perpetuation of the original corner position. No other improvements were made to this monument.

From the corner of sections 14, 15, 22, and 23.

S. 89° 03.7' W., between sections 15 and 22.

39.805 Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S15</u>
	S22
	1997

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

Corner is located in farmed pasture land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

79.610

The corner of sections 15, 16, 21, and 22, monumented with a plainly marked quartzite stone, 22x14xx14 inches, laying loose in a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T14S R1W	
S16	S15
S21	S22
1997	

A Deep-1 magnet was buried at base of aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Deposit quartzite stone alongside the aluminum post.

Corner is located 1 ft. west of old fence line, bearing N and S.

N. 1° 26.5' W., between sections 15 and 16.

20.030

Point for the S 1/16 section corner of section 15 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a collar of stone to top of aluminum cap marked:

T14S R1W	
S 1/16	
	S15
1997	

A Deep-1 magnet was buried at base of aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 51 ft. south of old 5 strand barbed wire fence line, bearing E and W.

40.060

The 1/4 section corner of section 15 only, monumented with an aluminum post, 2 1/2 inches diameter, projecting 3 inches above ground, with aluminum cap marked as described in the official record of the 1993 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 10 and 15, monumented with a limestone, 13x11x7 inches firmly set, and marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T14S R1W
1/4 S10
 S15
 1997

Corner is located on an ESE slope in sagebrush and juniper.

N. 89° 17.5' W., between sections 10 and 15.

40.397

The corner of sections 10 and 15 only, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above ground, with a mound of stone, 3 ft. base, 2 ft. high, to the east, with aluminum cap marked as described in the official record of the 1993 resurvey.

From the corner of sections 3 and 10 only, monumented with an aluminum post, 2 1/2 inches diameter, projecting 4 inches above ground, and in a mound of stone, 3 ft. base, 2 ft. high to the east, with aluminum cap marked as described in the official record of the 1993 resurvey.

From this corner, the closing corner of sections 4 and 9, monumented with an aluminum post, 2 1/2 inches diameter, in a mound of stone, with 4 ft. base to top of aluminum cap marked as described in the official record of the 1993 resurvey, bears S. 0° 38.1' E., 2.801 chains distance.

N. 0° 21.1' W., between sections 3 and 4.

37.765

Point for the E 1/4 section corner of section 4 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T14S R1W
1/4 |
 S4 |
 1997

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on a SW slope among scattered juniper.

40.560

Point for the 1/4 section corner of section 3 only, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R1W
| 1/4
| S3
1997

Raise a mound of stone, 4 ft. base, 2 ft. high, east of the corner.

Corner is located on top of a ridge, bears N. 60° E. and S. 40' W., and on old fire trail, 10 ft. wide.

82.620

The closing corner of sections 3 and 4, on the north boundary of the township, hereinbefore described.

From the corner of sections 4, 5, 8, and 9, monumented with an aluminum post, 2 1/2 inches diameter, firmly set in a mound of stone, 4 ft. base, to top of aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 15.3' W., between sections 4 and 5.

19.568

Point for the S 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T14S R1W
S 1/16
S5 | S4
1997

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Corner is located on top of spur, bears N. 70° E. and S. 70° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.136

The 1/4 section corner of sections 4 and 5, monumented with a trachyte stone, 16x12x7 inches, with a 1/4 dimly chiseled on the W face, and a scattered mound of stone, 2 1/2 ft. diameter, to the west.

There is no remaining evidence of the original bearing trees in area due to many burns.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T14S R1W
1/4
S5 | S4
1997

Deposit trachyte stone on north side of aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, east of the corner.

Corner is located on a steep NE slope in grass and scattered junipers.

Reestablishment of the Survey Executed by Stewart and Stewart
in 1898, and the Resurvey Executed by
F.D. Reynolds in 1993

From the 100 1/16 section corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 inches diameter, projecting 4 inches above ground, a mound of stone to the N and at S and E fence corner, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 89° 58.7' W., bet. sections 19 and 30.

20.164 Point for the 120 1/16 section corner of sections 19 and 30; not monumented.

60.492 Point for the 160 1/16 section corner of sections 19 and 30; not monumented.

80.656 The 180 1/16 section corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 inches diameter, projecting 3 inches above ground, and a mound of stone to the N, with aluminum cap marked as described in the official record of the 1993 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
Stewart and Stewart in 1898

From the corner of sections 17, 18, 19, and 20, monumented with an aluminum post, 2 1/2 inches diameter, projecting 3 inches above ground, with aluminum cap marked as described in the official record of the 1993 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

S. 89° 40.8' W., bet. sections 18 and 19.

40.273 Point for the 1/4 section corner of sections 18 and 19, at proportionate distance; there is no remaining evidence of the original monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
1/4 $\frac{S18}{S19}$
1996

Set a 6 ft. steel fence post alongside the aluminum post.

60.409 Point for the W 1/16 section corner of sections 18 and 19; not monumented.

80.545 Point for the 80 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
80 1/16 $\frac{S18}{S19}$
1996

Set a 6 ft. steel fence post alongside the aluminum post.

100.681 Point for the 100 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W

$$100 \frac{1}{16} \frac{S18}{S19}$$

1996

Set a 6 ft. steel fence post alongside the aluminum post.

140.953 Point for the 140 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W

$$140 \frac{1}{16} \frac{S18}{S19}$$

1996

Set a 6 ft. steel fence post alongside the aluminum post.

161.089 Point for the 160 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W

$$160 \frac{1}{16} \frac{S18}{S19}$$

1996

Set a 6 ft. steel fence post alongside the aluminum post.

181.225 Point for the 180 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, with 3 1/2 ft. base, to top of aluminum cap marked:

T14S R1W

$$180 \frac{1}{16} \frac{S18}{S19}$$

1996

Set a 6 ft. steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

205.761

The closing corner of sections 18 and 19, monumented with a 1986 Juab County aluminum post, 2 1/2 inches diameter, firmly set in the ground, and in a N and S fence line, with aluminum cap marked:

JUAB COUNTY		
T14S		
R2W	24	$\frac{18}{19}$
		1986

This corner is accepted as the best available evidence of the original corner position.

This corner will now function as a witness closing corner for the true point on the west boundary of the township.

No additional markings were added to this corner.

205.829

Intersect the east boundary of section 24, at the true point for the closing corner of sections 18 and 19.

The Subdivision of Section 4,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 9, monumented with an aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 1° 02.3' W., on the N-S center line of section 4.

20.016

Point for the center S 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W	
	C
S 1/16	S4
	C
	1997

40.032

Point for the center 1/4 section corner of section 4, at intersection with the E-W center line.

THE SUBDIVISION OF SECTION 4,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T14S R1W
C 1/4
S4
1997

Corner is located 15 lks. N of a ridge, bears E and W, which also has a fire trail 10 ft. wide on top, bears E and W.

84.904 The N 1/4 section corner of section 4, hereinbefore described.

From the E 1/4 section corner of section 4.

S. 89° 13.1' W., on the E-W center line of section 4.

39.145 The center 1/4 section corner of section 4.

58.653 Point for the center W 1/16 section corner of section 4; not monumented.

78.161 The 1/4 section corner of sections 4 and 5.

From the W 1/16 section corner of sections 4 and 9, monumented with an aluminum post, 2 1/2 inches diameter, projecting 5 inches above ground, and a mound of stone, 3 ft. base, 2 ft. high, to North of corner, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 38.7' W., on the N-S center line of the SW 1/4 of section 4.

19.786 Point for the SW 1/16 section corner of section 4, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
SW 1/16
S4
1997

Corner is located on a steep NE slope in scattered juniper and grass.

39.578 Point for the center W 1/16 section corner of section 4.

THE SUBDIVISION OF SECTION 4,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center S 1/16 section corner of section 4.

S. 89° 52.3' W., on the E-W center line of the SW 1/4 of section 4.

19.647 The SW 1/16 section corner of section 4.

39.290 The S 1/16 section corner of sections 4 and 5.

The Subdivision of Section 5,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 5 and 8, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with a mound of stone, 3 ft. base, 2 ft. high, north of corner, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 1° 26.3' W., on the N-S center line of section 5.

19.649 Point for the center S 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T14S R1W
C
S 1/16 | S5
C
1997

Corner is located on a gradual east slope among grass and scattered juniper, and about 1 chain west of draw, drains S.

39.298 Point for the center 1/4 section corner of section 5, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

T14S R1W
C 1/4
S5
1997

83.697 The N 1/4 section corner of section 5, hereinbefore described.

THE SUBDIVISION OF SECTION 5,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 4 and 5.

S. 89° 56.9' W., on the E-W center line of section 5.

40.153 The center 1/4 section corner of section 5.

80.240 The 1/4 section corner of sections 5 and 6, monumented with a quartzite stone, 16x10x9 inches, plainly marked and firmly set, with 1/4 on west face and a mound of stone to the west.

There is no remaining evidence of the original bearing trees.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
1/4
S6 | S5
1997

Deposit the quartzite stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Corner is located on a north slope in grass and juniper.

From the S 1/16 section corner of sections 4 and 5.

S. 89° 50.4' W., on the E-W center line of the SE 1/4 of section 5.

39.749 The center S 1/16 section corner of section 5.

The Subdivision of Section 10,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 1° 06.6' W., on the N-S center line of section 10.

41.256 Point for the center 1/4 section corner of section 10, at intersection with the E-W center line.

THE SUBDIVISION OF SECTION 10,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
C 1/4 S10
1997

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, , 2 ft. high, west of the corner.

Corner is located on N slope in dense juniper, and 42 ft. N of fence corner, with fences bearing E, W, and S.

82.647 The 1/4 section corner of sections 3 and 10, monumented with a quartzite stone, 16x8x5 inches, marked with 1/4 on N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
1/4 S3
S10
1997

Raise a mound of stone, 3 ft. base, , 2 ft. high, north of the corner.

From this corner, the corner of sections 3 and 10 only, bears S. 86° 12.7' W., 39.741 chains distance.

From the point for the 1/4 section corner of sections 10 and 11.

S. 88° 34.7' W., on the E-W center line of section 10.

39.304 The center 1/4 section corner of section 10.

79.335 The W 1/4 section corner of section 10, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above ground, with a mound of stone, 3 ft. base, 2 ft. high, east of the corner, with aluminum cap marked as described in the official record of the 1993 resurvey.

THE SUBDIVISION OF SECTION 15,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 15,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0° 35.0' W., on the N-S center line of section 15.

19.985 Point for the center S 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

C
S 1/16 | S15
C
1997

A Deep-1 magnet was buried at base of aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 51 ft, south of old 5 strand barbed wire fence, bears E and W.

39.970 Point for the center 1/4 section corner of section 15, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T14S R1W
C 1/4 S15
1997

Set a 6 ft. steel fence post alongside the aluminum post.

79.264 The 1/4 section corner of sections 10 and 15.

From the 1/4 section corner of sections 14 and 15.

S. 89° 11.5' W., on the E-W center line of section 15.

39.793 The center 1/4 section corner of section 15.

80.193 The W 1/4 section corner of section 15.

From the center S 1/16 section corner of section 15.

THE SUBDIVISION OF SECTION 15,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 07.7' W., on the E-W center line of the SW 1/4 of section 15.

40.102 The S 1/16 section corner of section 15 only.

The Subdivision of Section 18,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 18 and 19.

N. 0° 01.4' E., on the N-S center line of section 18.

19.903 Point for the center S 1/16 section corner of section 18; not monumented.

39.806 Point for the center 1/4 section corner of section 18, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
C 1/4
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

60.044 Point for the center N 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T14S R1W
C
N 1/16 | S18
C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

80.282 The 1/4 section corner of sections 7 and 18, monumented with a aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1991 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 18,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 17 and 18, monumented with an aluminum post, 2 1/2 inches diameter, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1993 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone west of the aluminum post.

S. 89° 39.0' W., on the E-W center line of section 18.

20.080 Point for the center E 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R1W
C — E 1/16 — C
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.160 The center 1/4 section corner of section 18.

60.318 Point for the center W 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
C — W 1/16 — C
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the aluminum post.

80.476 Point for the center 80 1/16 section corner of section 18; not monumented.

100.634 Point for the center 100 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 18,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

$$\begin{array}{c} \text{T14S R1W} \\ \text{C } \frac{100 \ 1/16}{\text{S18}} \text{ C} \\ 1996 \end{array}$$

Set a 6 ft. steel fence post alongside the aluminum post.

140.950 Point for the center 140 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

$$\begin{array}{c} \text{T14S R1W} \\ \text{C } \frac{140 \ 1/16}{\text{S18}} \text{ C} \\ 1996 \end{array}$$

Set a 6 ft. steel fence post alongside the aluminum post.

181.266 Point for the center 180 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T14S R1W} \\ \text{C } \frac{180 \ 1/16}{\text{S18}} \text{ C} \\ 1996 \end{array}$$

205.743 The 1/4 section corner of section 18 only, on the west boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 18.

N. 0° 13.2' W., on the N-S center line of the NE 1/4 of section 18.

40.341 The E 1/16 section corner of sections 7 and 18, monumented with an aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, in a collar of stone, with aluminum cap marked as described in the official record of the 1991 resurvey.

From the point for the W 1/16 section corner of sections 18 and 19; not monumented.

N. 0° 00.5' W., on the N-S center line of the SW 1/4 of section 18.

THE SUBDIVISION OF SECTION 18,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**19.898**

The SW 1/16 section corner of section 18, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R1W
SW 1/16
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.796

The center W 1/16 section corner of section 18.

From the 80 1/16 section corner of sections 18 and 19.

N. 0° 02.6' W., on the N-S 80 1/16 line of the SW 1/4 of section 18.

19.893

The S 80 1/16 section corner of section 18, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, in a mound of stone, 6 ft. base, to top of aluminum cap marked:

T14S R1W
S 80 1/16
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.786

Point for the center W 80 1/16 section corner of section 18; not monumented.

From the 100 1/16 section corner of sections 18 and 19.

N. 0° 04.6' W., on the N-S 100 1/16 line of the SW 1/4 of section 18.

19.888

The S 100 1/16 section corner of section 18, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 18,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W
S 100 1/16
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.776 The center 100 1/16 section corner of section 18.

From the 140 1/16 section corner of sections 18 and 19.

N. 0° 08.7' W., on the N-S 140 1/16 line of the SW 1/4 of section 18.

19.877 The S 140 1/16 section corner of section 18, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R1W
S 140 1/16
S18
1996

39.754 The center 140 1/16 section corner of section 18.

From the 180 1/16 section corner of sections 18 and 19.

N. 0° 12.7' W., on the N-S 180 1/16 line of the SW 1/4 of section 18.

19.867 The S 180 1/16 section corner of section 18, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R1W
S 180 1/16
S18
1996

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

39.734 The center 180 1/16 section corner of section 18.

THE SUBDIVISION OF SECTION 18,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the center S 1/16 section corner of section 18; not monumented.

S. 89° 39.9' W., on the E-W center line of the SW 1/4 of section 18.

20.147 The SW 1/16 section corner of section 18.

40.294 The S 80 1/16 section corner of the SW 1/4 of section 18.

60.441 The S 100 1/16 section corner of the SW 1/4 of section 18.

100.735 The S 140 1/16 section corner of the SW 1/4 of section 18.

141.029 The S 180 1/16 section corner of the SW 1/4 of section 18.

165.555 The S 1/16 section corner of section 18 only, on the west boundary of the township, hereinbefore described.

From the center 100 1/16 section corner of section 18.

N. 0° 05.6' W., on the N-S 100 1/16 line of the NW 1/4 of section 18.

20.100 The N 100 1/16 section corner of section 18, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
N 100 1/16
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.209 The 100 1/16 section corner of sections 7 and 18, monumented with an aluminum post, 2 1/2 inches diameter, projecting 4 inches above ground, a steel fence post alongside, with aluminum cap marked as described in the official record of the 1991 resurvey.

From the center 140 1/16 section corner of section 18.

N. 0° 09.6' W., on the N-S 140 1/16 line of the NW 1/4 of section 18.

20.008 The N 140 1/16 section corner of section 18, at intersection with the E-W center line of the NW 1/4.

THE SUBDIVISION OF SECTION 18,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
N 140 1/16
S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.022 The 140 1/16 section corner of sections 7 and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above ground, with a mound of stone, 4 ft. base, 2 ft. high, north of the corner, with aluminum cap marked as described in the official record of the 1991 resurvey.

From the center N 1/16 section corner of section 18.

S. 89° 31.2' W., on the E-W center line of the NW 1/4 of section 18.

60.511 The N 100 1/16 section corner of the NW 1/4 of section 18.

100.849 The N 140 1/16 section corner of the NW 1/4 of section 18.

165.645 The N 1/16 section corner of section 18 only, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 19,
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 inches diameter, projecting 2 inches above ground, in an E and W fence line, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 40.6' W., on the N-S center line of section 19.

19.840 Point for the center S 1/16 section corner of section 19; not monumented.

39.680 Point for the center 1/4 section corner of section 19, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 19,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W
C 1/4 S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

59.957 Point for the center N 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
C
N 1/16 | S19
C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

80.234 The 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20, monumented with an aluminum post, 2 1/2 inches diameter, firmly set and projecting 3 inches above ground, with aluminum cap marked as described in the official record of the 1993 resurvey.

Set a 6 ft. steel fence post alongside the aluminum post.

This corner will also function as a B.L.M. control station, hereinbefore described.

West, on the E-W center line of section 19.

40.563 The center 1/4 section corner of section 19.

60.729 Point for the center W 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
C — W 1/16 — C
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

80.895 Point for the center 80 1/16 section corner of section 19; not monumented.

THE SUBDIVISION OF SECTION 19,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS
101.061

Point for the center 100 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

$$\begin{array}{c} \text{T14S R1W} \\ \text{C} \frac{\text{S19}}{100 \quad 1/16} \text{C} \\ 1996 \end{array}$$

Set a 6 ft. steel fence post alongside the aluminum post.

161.559

Point for the center 160 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T14S R1W} \\ \text{C} \frac{160 \quad 1/16}{\text{S19}} \text{C} \\ 1996 \end{array}$$

Set a 6 ft. steel fence post alongside the aluminum post.

181.725

Point for the center 180 1/16 section corner of section 19; not monumented.

206.841

The 1/4 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

From the W 1/16 section corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 inches diameter, projecting 2 inches above ground, in an E and W fence line, and a mound of stone to the N, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 40.9' W., on the N-S center line of the SW 1/4 of section 19.

19.829

Point for the SW 1/16 section corner of section 19, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T14S R1W} \\ \text{SW } 1/16 \quad \text{S19} \\ 1996 \end{array}$$

THE SUBDIVISION OF SECTION 19,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

39.667

The center W 1/16 section corner of section 19.

From the 100 1/16 section corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 inches diameter, projecting 4 inches above ground, at S and E fence corner, and a mound of stone to the N, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 42.1' W., on the N-S 100 1/16 line of the SW 1/4 of section 19.

19.834

Point for the S 100 1/16 section corner of the SW 1/4 of section 19, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R1W
S 100 1/16
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.666

The center 100 1/16 section corner of section 19.

From the point for the 160 1/16 section corner of sections 19 and 30; not monumented.

N. 0° 42.7' W., on the N-S 160 1/16 line of the SW 1/4 of section 19.

19.820

Point for the S 160 1/16 section corner of the SW 1/4 of section 19, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
S 160 1/16
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 3 ft. high, south of aluminum post.

THE SUBDIVISION OF SECTION 19,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**39.643**

The center 160 1/16 section corner of section 19.

From the 180 1/16 section corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 inches diameter, 3 inches above ground, and a mound of stone to the N, with aluminum cap marked as described in the official record of the 1993 resurvey.

N. 0° 43.2' W., on the N-S 180 1/16 line of the SW 1/4 of section 19.

19.815

Point for the S 180 1/16 section corner of the SW 1/4 of section 19, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R1W
S 180 1/16
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.635

Point for the center 180 1/16 section corner of section 19; not monumented.

From the point for the center S 1/16 section corner of section 19; not monumented.

N. 89° 59.5' W., on the E-W center line of the SW 1/4 of section 19.

20.165

The SW 1/16 section corner of section 19.

60.493

The S 100 1/16 section corner of the SW 1/4 of section 19.

120.989

The S 160 1/16 section corner of the SW 1/4 of section 19.

141.154

The S 180 1/16 section corner of the SW 1/4 of section 19.

166.583

Point for the S 1/16 section corner of section 19 only, on the west boundary of the township; not monumented.

From the point for the center 80 1/16 section corner of section 19; not monumented.

N. 0° 36.1' W., on the N-S 80 1/16 line of the NW 1/4 of section 19.

THE SUBDIVISION OF SECTION 19,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**20.164**

Point for the N 80 1/16 section corner of section 19, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
N 80 1/16
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.328

The 80 1/16 section corner of sections 18 and 19.

From the center 100 1/16 section corner of section 19.

N. 0° 33.8' W., on the N-S 100 1/16 line of the NW 1/4 of section 19.

20.108

Point for the N 100 1/16 section corner of the NW 1/4 of section 19, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R1W
N 100 1/16
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

40.216

The 100 1/16 section corner of sections 18 and 19.

From the center 160 1/16 section corner of section 19.

N. 0° 27.0' W., on the N-S 160 1/16 line of the NW 1/4 of section 19.

19.939

Point for the N 160 1/16 section corner of the NW 1/4 of section 19, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 19,
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W
N 160 1/16
S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

39.878

The 160 1/16 section corner of sections 18 and 19.

From the center N 1/16 section corner of section 19.

S. 89° 50.5' W., on the E-W center line of the NW 1/4 of section 19.

40.303

The N 80 1/16 section corner of the NW 1/4 of section 19.

60.454

The N 100 1/16 section corner of the NW 1/4 of section 19.

120.907

The N 160 1/16 section corner of the NW 1/4 of section 19.

165.886

Point for the N 1/16 section corner of section 19 only, on the west boundary of the township;
not monumented.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Richard Houston	Cadastral Surveyor
Steven J. Oatman	Surveying Technician
Nathan James	Survey Aid

CERTIFICATE OF SURVEY

We, *M. Ross Workman and Ronald K. Baugh*, Supervisory Cadastral Surveyors, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *30th day of August, 1996*, we have *dependently resurveyed portions of the west and north boundaries and a portion of the subdivisional lines, and subdivided sections 4, 5, 10, 15, 18, and 19 in Township 14 South, Range 1 West*,

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 16, 1998

Date

March 16, 1998

Date

M. Ross Workman

(Supervisory Cadastral Surveyor)

Ronald K. Baugh

(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the west and north boundaries, a portion of the subdivisional lines and the subdivision of sections 4, 5, 10, 15, 18, and 19 in Township 14 South, Range 1 West, Salt Lake Meridian, Utah*,

executed by *M. Ross Workman and Ronald K. Baugh*, Supervisory Cadastral Surveyors

having been critically examined and found correct, are hereby approved.

March 18, 1998

Date

Daniel W. Wehl

(Chief Cadastral Surveyor for Utah)